


Datenblatt/Datasheet

QTPX7 - Programmable Oscillator -

Enclosure
SMD 7x5

Date: 22.10.2014
ROHS-compliance

Dimensions



PIN CONNECTIONS

- 1 Control
- 2 GND
- 3 RF Output
- 4 V_{DD}

Parameter	MIN	TYP	MAX	UNIT	NOTE
Frequency range	1.5		200	MHz	
Frequency stability					
Nominal tolerance	± 5		± 20	ppm	adjustable
vs. Temperature in the operating temp. range	± 5		± 50	ppm	
vs. supply voltage				ppm	
vs. load change				ppm	
aging			< ± 5	ppm	+25°C, 1 st year
Supply voltage		2.7/3.3/ 5.0		V	
Current consumption			35	mA	
RF output					
Signal waveform		HCMOS			
Load		30 / 15		pF	(1)
Duty cycle	45		55	%	
Rise / fall time			4.0	ns	
Start-up time		3	10	ms	
Operating temperature range	- 40		+ 85	°C	
Storage temperature range	- 55		+ 125	°C	
Phase noise				dB _c /Hz	at 100 Hz
Enclosure	SMD 7x5				(see drawing)
ESD rating (HBM)				kV	

Note: ⁽¹⁾ frequency dependent, 30 pF up to 40 MHz



Quarztechnik Daun GmbH

Quartz Crystals · Oscillators · Sensor Technology

Alte Darscheider Str. 15
54550 Daun · Germany

Phone: +49 0 6592-92070
Fax: +49 0 6592-7670

info@quarztechnik.com
www.quarztechnik.com

