




Enclosure
DIL 8

Date: 22.10.2014
ROHS-compliance

Dimensions



PIN CONNECTIONS

- 1 NC
- 2 GND
- 3 RF Output
- 4 V_{DD}



Parameter	MIN	TYP	MAX	UNIT	NOTE
Frequency range	9		110	MHz	
Frequency stability					
Nominal tolerance	± 5		± 20	ppm	
vs. Temperature in the operating temp. range	± 5		± 50	ppm	
vs. supply voltage			± 2	ppm	
vs. load change			± 2	ppm	
aging			< ± 3	ppm	+25°C, 1 st year
Supply voltage		3.3 5.0		V	
Current consumption	20		40	mA	(1)
RF output					
Signal waveform		HCMOS			
Load		15		pF	
Duty cycle	45		55	%	
Rise / fall time			10	ns	
Start-up time			10	ms	
Operating temperature range	- 40		+ 85	°C	
Storage temperature range	- 55		+ 125	°C	
Phase noise		< -120		dB _c /Hz	at 100 Hz
Enclosure	DIL 8				(see drawing)
ESD rating (HBM)			1.5	kV	

Note: (1) frequency dependent



Quarztechnik Daun GmbH

Quartz Crystals · Oscillators · Sensor Technology

Alte Darscheider Str. 15
54550 Daun · Germany

Phone: +49 0 6592-92070
Fax: +49 0 6592-7670

info@quarztechnik.com
www.quarztechnik.com

